

气凝胶绝热毡 FMA650

Aerogel Blanket FMA650

Specification
产品规格

厚度 Thickness	FMA650-3	3mm
	FMA650-6	6mm
	FMA650-10	10mm
长度 Length	FMA650-3	34m
	FMA650-6	34m
	FMA650-10	25m
宽度 Width	1500mm	
颜色 Color	白色 White	
推荐使用温度 Suggested Working Temperature	-50~650℃	
说明：可根据客户要求定制。 Notes: Sizes could be on customers' requirement.		



性能参数 Technical Data	尺寸稳定性 Size Stability	1%	GB/T 8811
	热荷重收缩温度 Shrinkage Temperature under Pressure	800℃	
	压缩性能 Compressive Property	@10% 60KPa @20% 120KPa	GB/T 13480
	燃烧等级 Fire Rating	A1	GB/T 5460
	拉伸强度 Tensile Strength		GB/T 17911
	导热系数 Thermal Conductivity	25℃	0.020
		200℃	0.025
		300℃	0.035
		400℃	0.046
		500℃	0.058
用途 Function	300℃至650℃的高温管道设备保温 For 300℃~650℃ pipes or equipment insulation		
	超高压蒸汽管道设备保温、工业窑炉保温 Super pressure vapor pipes and equipment insulation, industrial furnace insulation		